## **Expansion of Copper Tube Data Sheet**



## **Expansion of Copper Tube**

Copper has a coefficient of linear expansion of 17 x 10-6oC. for example, a 10 metre length of copper tube carrying hot water at 600C will increase in length by almost 7mm when heated from 200C. Assuming that temperature cycling of the system is 200C, thaere will be a continuous cycle of expansion and contration of 3.4mm. refer to table below.

## **Copper Tube Expansion**



Temperature	Tube Length									
Change	3m	4m	5m	6m	7m	8m	9m	10m	12m	25m
10°	0.5mm	0.7mm	0.9mm	1.0mm	1.2mm	1.4mm	1.5mm	1.7mm	2.0mm	4.3mm
20°	1.0mm	1.4mm	1.7mm	2.0mm	2.4mm	2.7mm	3.0mm	3.4mm	4.0mm	8.5mm
30°	1.5mm	2.0mm	2.6mm	3.1mm	3.6mm	4.1mm	4.6mm	5.1mm	6.1mm	13.0mm
40°	2.0mm	2.7mm	3.4mm	4.1mm	4.8mm	5.4mm	6.1mm	6.8mm	8.2mm	17.0mm
50°	2.6mm	3.4mm	4.3mm	5.1mm	6.0mm	6.8mm	7.7mm	8.5mm	10.2mm	21.0mm
60°	3.1mm	4.1mm	5.1mm	6.1mm	7.1mm	8.2mm	9.2mm	10.2mm	12.2mm	26.0mm
70°	3.6mm	4.8mm	6.0mm	7.1mm	8.3mm	9.5mm	10.7mm	11.9mm	14.3mm	30.0mm
80°	4.1mm	5.4mm	6.8mm	8.2mm	9.5mm	10.9mm	12.2mm	13.6mm	16.3mm	34.0mm
90°	4.6mm	6.1mm	7.7mm	9.2mm	10.7mm	12.2mm	13.8mm	15.3mm	18.4mm	38.0mm
100°	5.1mm	6.8mm	8.5mm	10.2mm	11.9mm	13.6mm	15.3mm	17.0mm	20.4mm	43.0mm
150°	7.65mm	10.2mm	12.75mm	15.3mm	17.85mm	20.4mm	22.95mm	25.5mm	30.6mm	63.75mm
200°	10.2mm	13.6mm	17.0mm	20.4mm	23.8mm	27.2mm	30.6mm	34.0mm	40.8mm	85.0mm

