



Class B Fire Rated Pre-Insulated Coil

A fast and easy solution that meets the needs of Euroclass EN 13501-1 Rating of BL-s1,d0

- Backed by Lawton's reputation for quality, service and customer care for over 100 years
- Meets European Building and Fire Safety Regulations
- Class B tested and certified for complete peace of mind
- PE Foam B rated insulation matched with Lawton Copper tube gives total product confidence
- Suitable for Heat Pump and Air Conditioning applications
- Available in 20 and 25mtr coils, in both 9mm and 13mm thickness
- Easy installation. No glue, tape or messy powder
- Using pre insulated coil achieves pipework installation in less than half the time of conventional methods
- New improved profile developed for easy splitting during installation

Pair Coil

Part Number	Product Description	Tube Dimensions	Temper	Insulation Thickness	Lengths	Pallet Qty (coils)	Kgs per Coil
LPC1438CB-9MM	9mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 3/8" x 0.81mm	Soft	9mm (3/8")	25m	11	6.45
LPC1412CB-9MM	9mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 1/2" x 0.81mm	Soft	9mm (3/8")	25m	11	7.22
LPC1458CB-9MM	9mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 5/8" x 0.91mm	Soft	9mm (3/8")	25m	11	9.32
LPC3858CB-9MM	9mm Lawton Pair Coil Class 0 Fire Rated	3/8" x 0.81mm & 5/8" x 0.91mm	Soft	9mm (3/8")	25m	10	10.93
LPC1438CB-13MM	13mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 3/8" x 0.81mm	Soft	13mm (1/2")	20m	11	6.48
LPC1412CB-13MM	13mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 1/2" x 0.81mm	Soft	13mm (1/2")	20m	10	7.25
LPC1458CB-13MM	13mm Lawton Pair Coil Class 0 Fire Rated	1/4" x 0.71mm & 5/8" x 0.91mm	Soft	13mm (1/2")	20m	10	9.36
LPC3858CB-13MM	13mm Lawton Pair Coil Class 0 Fire Rated	3/8" x 0.81mm & 5/8" x 0.91mm	Soft	13mm (1/2")	20m	9	10.98