



Class B Fire Rated Pre-Insulated Coil

A fast and easy solution that meets the needs of Euroclass EN 13501-1 Rating of BL-s1,d0

- Backed by Lawton's reputation for quality, service and customer care for over 100 years
- Meets European Building and Fire Safety Regulations
- Class B tested and certified for complete peace of mind
- PE Foam B rated insulation matched with Lawton Copper tube gives total product confidence
- Suitable for Heat Pump and Air Conditioning applications
- Available in 20 and 25mtr coils, in 9mm thickness
- Easy installation. No glue, tape or messy powder
- Using pre insulated coil achieves pipework installation in less than half the time of conventional methods
- New improved profile developed for easy splitting during installation

Pair Coil

Part Number	Product Description	Tube Dimensions	Temper	Insulation Thickness	Lengths	Pallet Qty (coils)	Kgs per Coil
B1001	9mm Lawton Pair Coil Class B Fire Rated	1/4" x 0.71mm & 3/8" x 0.81mm	Soft	9mm (3/8")	25m	11	6.45
B1002	9mm Lawton Pair Coil Class B Fire Rated	1/4" x 0.71mm & 1/2" x 0.81mm	Soft	9mm (3/8")	25m	11	7.22
B1003	9mm Lawton Pair Coil Class B Fire Rated	1/4" x 0.71mm & 5/8" x 0.91mm	Soft	9mm (3/8")	25m	11	9.32
B1004	9mm Lawton Pair Coil Class B Fire Rated	3/8" x 0.81mm & 5/8" x 0.91mm	Soft	9mm (3/8")	25m	10	10.93